

RSAM data sheet RSAM-1060-32ps-x, $\lambda = 1060$ nm

RSAM - Resonant saturable absorber mirror

Working wavelength	$\lambda = 1056 \dots 1064$ nm (angle and temperature dependent)
Full Width at Half Maximum	FWHM = 20 nm
Low intensity absorptance	$A \geq 98$ %
Low intensity reflectance	$R_{\min} \leq 2$ %
Saturation fluence	$\Phi_{\text{sat}} = 30$ $\mu\text{J}/\text{cm}^2$
Relaxation time constant	$\tau = 32$ ps
Non-saturable loss	$A_{\text{ns}} = 40$ %
Chip area	4.0 mm x 4.0 mm; other dimensions on request
Chip thickness	450 μm
Front side	dielectric cover
Mounting of RSAM-1060-x	denotes the type of mounting as follows:
x = 0	unmounted
x = 12.7 g	glued on a gold plated Cu-cylinder with 12.7 mm \varnothing
x = 25.4 g	glued on a gold plated Cu-cylinder with 25.4 mm \varnothing
x = 12.7 s	soldered on a gold plated Cu-cylinder with 12.7 mm \varnothing
x = 25.4 s	soldered on a gold plated Cu-cylinder with 25.4 mm \varnothing
x = 25.0 w	soldered on a water cooled Cu-cylinder with 25.0 mm \varnothing
x = FC	mounted on a 1 m monomode fiber cable with FC/PC connector
x = FC/PC with TEC	mounted on a 1 m monomode fiber cable with FC/PC or other connector type and TEC (thermoelectric cooler) for fine tuning of the resonance wavelength

Unsaturated spectral reflectance

